



Power Management for i.MX50/53 Processors

MC34708

新規採用非推奨


このページでは、新規設計を推奨しない製品に関する情報を掲載しています。

Last Updated: May 25, 2023

The MC34708 is not recommended for new designs. We recommend using the MMPF0100 or MC34709.

MC34708 is the PMIC designed specifically for use with the NXP i.MX50 and i.MX53 processor families (Mature processors). It is available in a 8 x 8 and 13 x 13 mm MAPBGA and supports an ambient operating temperature range of -40 to 85 deg. C for various consumer applications. As the companion PMIC on several i.MX reference designs, it is a proven solution, which enables a faster time to market with fewer resources. It integrates six buck and eight LDO regulators to provide power for the processor core, memory and peripherals. A mini/micro USB switch supports USB, UART and audio inputs to help reduce the connector count for a more compact design. In addition, the MC34708 integrates a real-time clock, coin cell charger, 10-bit ADC, 5 V boost regulator for USB-OTG support, PWM generator, resistive touch screen interface, general purpose LED drivers and four GPIOs.

MC34708 Block Diagram



View additional information for [Power Management for i.MX50/53 Processors](#).

Note: The information on this document is subject to change without notice.

www.nxp.com

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2024 NXP B.V.