

S12Q Automotive and Industrial Microcontrollers (MCUs)

S12Q

新規採用非推奨

このページでは、新規設計を推奨しない製品に関する情報を掲載しています。

Last Updated: Apr 9, 2022

The MC9S12Q is an automotive MCU with up to 128 KB of embedded flash, giving you the power and flexibility of the 16-bit standard S12 core for a whole new range of cost-sensitive and space-constraint applications.

All family members feature full 16-bit data paths throughout.

The inclusion of a phase-lock look (PLL) circuit lets you adjust power consumption and performance to suit operational requirements.

In addition to the I/O ports available in each module, up to 10 dedicated I/O port bits are available with wake-up capability from stop or wait mode.

S12Q Microcontroller Block Diagram Block Diagram

HCS12 CPU 16 MHz	1 CAN
32K-128K Flash/ROM	1 SCI/LIN
Up to 4K RAM	1 SPI
CRG	KWI
	4-ch., 16-bit PWM
INT	6-ch., 16-bit
DBG	Timer
BDM	8-ch., 10-bit ADC

View additional information for S12Q Automotive and Industrial Microcontrollers (MCUs).

Note: The information on this document is subject to change without notice.

www.nxp.comNXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2024 NXP B.V.