



i.MX RT1180: Crossover MCU with TSN Switch and EdgeLock®

i.MX-RT1180-TEST


Last Updated: Sep 24, 2025

i.MX RT1180 Crossover MCUs are dual-core, real-time microcontrollers (MCUs) featuring an Arm® Cortex®-M7 and Arm® Cortex®M33 for high performance and real-time functionality. The i.MX RT1180 includes an integrated Gbps time-sensitive networking (TSN) switch and EtherCAT SubDevice Controller making it ideal for industrial applications.

The i.MX RT1180 CM7 operates at up to 800 MHz and the Arm Cortex-M33 up to 300 MHz with 1.5 MB on-chip RAM. The family supports multiple protocols, bridging communications between real-time Ethernet and Industry 4.0 systems. The i.MX RT1180 offers advanced security with the integrated EdgeLock® Secure Enclave.

The i.MX RT1180 family is supported by the MCUXpresso developer experience, which includes an SDK, a choice of IDEs and secure provisioning and configuration tools to enable rapid development.

i.MX RT1180 Crossover MCU Block Diagram



View additional information for [i.MX RT1180: Crossover MCU with TSN Switch and EdgeLock®](#).

Note: The information on this document is subject to change without notice.

www.nxp.com

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2025 NXP B.V.