
MCUXpresso SDK Release Notes Supporting Ipcxpresso55s36

Change Logs

NXP Semiconductors



Contents

Driver Change Log

COMMON	1
LPADC	3
PRINCE	4
RNG	5

Middleware Change Log

emWin library	6
FatFs for MCUXpresso SDK	6
FreeMASTER Communication Driver	7
MBEDTLS for MCUXpresso SDK	8
NTAG I2C plus library	9
Trusted Firmware M (TF-M) for MCUXpresso SDK	9
USB stack for MCUXpresso SDK	10

Component Change Log

CODEC	17
SERIAL_MANAGER	18

1 Driver Change Log

COMMON

The current COMMON driver version is 2.4.0.

- 2.4.0
 - New Features
 - * Added EnableIRQWithPriority, IRQ_SetPriority, and IRQ_ClearPendingIRQ for ARM.
 - * Added MSDK_EnableCpuCycleCounter, MSDK_GetCpuCycleCount for ARM.
- 2.3.3
 - New Features
 - * Added NETC into status group.
- 2.3.2
 - Improvements
 - * Make driver aarch64 compatible
- 2.3.1
 - Bug Fixes
 - * Fixed MAKE_VERSION overflow on 16-bit platforms.
- 2.3.0
 - Improvements
 - * Split the driver to common part and CPU architecture related part.
- 2.2.10
 - Bug Fixes
 - * Fixed the ATOMIC macros build error in cpp files.
- 2.2.9
 - Bug Fixes
 - * Fixed MISRA C-2012 issue, 5.6, 5.8, 8.4, 8.5, 8.6, 10.1, 10.4, 17.7, 21.3.
 - * Fixed SDK_Malloc issue that not allocate memory with required size.
- 2.2.8
 - Improvements
 - * Included stddef.h header file for MDK tool chain.
 - New Features:
 - * Added atomic modification macros.
- 2.2.7
 - Other Change
 - * Added MECC status group definition.
- 2.2.6
 - Other Change
 - * Added more status group definition.
 - Bug Fixes
 - * Undef __VECTOR_TABLE to avoid duplicate definition in cmsis_clang.h
- 2.2.5
 - Bug Fixes

- * Fixed MISRA C-2012 rule-15.5.
- 2.2.4
 - Bug Fixes
 - * Fixed MISRA C-2012 rule-10.4.
- 2.2.3
 - New Features
 - * Provided better accuracy of SDK_DelayAtLeastUs with DWT, use macro SDK_DELAY_USE_DWT to enable this feature.
 - * Modified the Cortex-M7 delay count divisor based on latest tests on RT series boards, this setting lets result be closer to actual delay time.
- 2.2.2
 - New Features
 - * Added include RTE_Components.h for CMSIS pack RTE.
- 2.2.1
 - Bug Fixes
 - * Fixed violation of MISRA C-2012 Rule 3.1, 10.1, 10.3, 10.4, 11.6, 11.9.
- 2.2.0
 - New Features
 - * Moved SDK_DelayAtLeastUs function from clock driver to common driver.
- 2.1.4
 - New Features
 - * Added OTFAD into status group.
- 2.1.3
 - Bug Fixes
 - * MISRA C-2012 issue fixed.
 - Fixed the rule: rule-10.3.
- 2.1.2
 - Improvements
 - * Add SUPPRESS_FALL_THROUGH_WARNING() macro for the usage of suppressing fallthrough warning.
- 2.1.1
 - Bug Fixes
 - * Deleted and optimized repeated macro.
- 2.1.0
 - New Features
 - * Added IRQ operation for XCC toolchain.
 - * Added group IDs for newly supported drivers.
- 2.0.2
 - Bug Fixes
 - * MISRA C-2012 issue fixed.
 - Fixed the rule: rule-10.4.
- 2.0.1
 - Improvements
 - * Removed the implementation of LPC8XX Enable/DisableDeepSleepIRQ() function.
 - * Added new feature macro switch "FSL_FEATURE_HAS_NO_NONCACHEABLE_S-

ECTION" for specific SoCs which have no noncacheable sections, that helps avoid an unnecessary complex in link file and the startup file.

- * Updated the align(x) to **attribute**(aligned(x)) to support MDK v6 armclang compiler.
- 2.0.0
 - Initial version.

LPADC

The current LPADC driver version is 2.6.2.

- 2.6.2
 - Bug Fixes -Fixed the violations of MISRA C-2012 rules. -Fixed LPADC driver code compile error issue.
- 2.6.1
 - Improvements
 - * Updated the use of macros in the driver code.
- 2.6.0
 - Improvements
 - * Added the API LPADC_SetOffset12BitValue() to configure 12bit ADC conversion offset trim value manually.
 - * Added the API LPADC_SetOffset16BitValue() to configure 16bit ADC conversion offset trim value manually.
 - * Added API to set offset calibration mode.
 - * Added configuration of alternate channel.
 - * Updated auto calibration API and added calibration value conversion API.
 - New feature
 - * Added API LPADC_EnableHardwareTriggerCommandSelection() to enable trigger commands controlled by ADC_ETC.
 - * Updated LPADC_DoAutoCalibration() to allow doing something else before the ADC initialization to be totally complete. Enhance initialization duration time of the ADC.
 - * Added two new APIs to get/set calibration value.
- 2.5.2
 - Improvements
 - * Added while loop, LPADC_GetConvResult() will return only when the FIFO will not be empty.
- 2.5.1
 - Bug Fixes
 - * Fixed some typos in Lpadc driver comments.
- 2.5.0
 - Improvements
 - * Added missing items to enable trigger interrupts.
- 2.4.0
 - New features
 - * Added APIs to get/clear trigger status flags.

- 2.3.0
 - Improvements
 - * Removed LPADC_MeasureTemperature() function for the LPADC supports different temperature sensor calculation equations.
- 2.2.1
 - Improvements
 - * Optimized LPADC_MeasureTemperature() function to support the specific series with flash solidified calibration value.
 - * Clean doxygen warnings.
 - Bug Fixes
 - * Fixed violations of MISRA C-2012 rule 10.3, rule 10.8 and rule 17.7.
- 2.2.0
 - New Feature
 - * Added API LPADC_MeasureTemperature() to get correct temperature from the internal sensor.
 - Improvements
 - * Separated lpadc_conversion_resolution_mode_t with related feature macro.
 - Bug Fixes
 - * Fixed the violations of MISRA C-2012 rules:
 - Rule 10.3, 10.4, 10.6, 10.7 and 17.7.
- 2.1.1
 - Improvements
 - * Updated the gain calibration formula.
 - * Used feature to segregate the new item kLPADC_TriggerPriorityPreemptSubsequently.
- 2.1.0
 - New Features
 - * Added the API LPADC_SetOffsetValue() to support configure offset trim value manually.
 - * Added the API LPADC_DoOffsetCalibration() to do offset calibration independently.
 - Improvements
 - * Improved the usage of macros and removed invalid macros.
- 2.0.2
 - Improvements
 - * Added support for platforms with 2 FIFOs and different calibration measures.
- 2.0.1
 - Bug Fixes
 - * Ensured the API LPADC_SetConvCommandConfig configure related registers correctly.
- 2.0.0
 - Initial version.

PRINCE

The current PRINCE driver version is 2.5.1.

- Version 2.6.0

- Renamed CSS to ELS.
- Version 2.5.1
 - Fix build error due to renamed symbols.
- Version 2.3.2
 - Fix documentation of enumeration.
 - Extend PRINCE example.
- Version 2.3.1
 - Fix MISRA-2012 issues.
 - Add support for LPC55S0x series
- Version 2.3.0
 - Add support for LPC55S1x and LPC55S2x series
- Version 2.2.0
 - Add runtime checking of the A0 and A1 rev. of LPC55Sxx serie to support both silicone revisions.
- Version 2.1.0
 - Update for the A1 rev. of LPC55Sxx serie.
- 2.0.0
 - Initial version.

RNG

The current RNG driver version is 2.0.3.

- 2.0.3
 - Modified RNG_Init and RNG_GetRandomData functions, added rng_accumulateEntropy and rng_readEntropy functions. These changes are reflecting recommended usage of RNG according to device UM
- 2.0.2
 - Add RESET_PeripheralReset function inside RNG_Init and RNG_Deinit functions.
- 2.0.1
 - Fix MISRA C-2012 issue.
- 2.0.0
 - Initial version.

2 Middleware Change Log

emWin library

The currently supported version is 6.32b

- v6.28_rev1
 - add cm33_nodsp_fpu libraries for Cortec M33 without DSP extension with SP FPU
- v6.28
 - upgraded to v6.28
- v6.24_rev2
 - add cm33_nodsp libraries for Cortex M33 without DSP extension
- v6.24_rev1
 - recompiled cm33 library with fpu single precision
 - added cm7_sp library for Cortex M7 with sp fpu for IAR
- v6.24
 - upgraded to v6.24
- v6.16c
 - upgraded to v6.16c
 - updated temperature_control demo generated by AppWizard
- v6.14d
 - upgraded to v6.14d
- v6.10f
 - upgraded to v6.10f

FatFs for MCUXpresso SDK

Current version is FatFs R0.14b_rev0.

- R0.14b_rev1
 - Applied patches from <http://elm-chan.org/fsw/ff/patches.html>
- R0.14b_rev0
 - Upgraded to version 0.14b
- R0.14a_rev0
 - Upgraded to version 0.14a
 - Applied patch ff14a_p1.diff and ff14a_p2.diff
- R0.14_rev0
 - Upgraded to version 0.14
 - Applied patch ff14_p1.diff and ff14_p2.diff
- R0.13c_rev0
 - Upgraded to version 0.13c
 - Applied patches ff_13c_p1.diff, ff_13c_p2.diff, ff_13c_p3.diff and ff_13c_p4.diff.
- R0.13b_rev0
 - Upgraded to version 0.13b

- R0.13a_rev0
 - Upgraded to version 0.13a. Added patch ff_13a_p1.diff.
- R0.12c_rev1
 - Add NAND disk support.
- R0.12c_rev0
 - Upgraded to version 0.12c and applied patches ff_12c_p1.diff and ff_12c_p2.diff.
- R0.12b_rev0
 - Upgraded to version 0.12b.
- R0.11a
 - Added glue functions for low-level drivers (SDHC, SDSPI, RAM, MMC). Modified diskio.c.
 - Added RTOS wrappers to make FatFs thread safe. Modified syscall.c.
 - Renamed ffconf.h to ffconf_template.h. Each application should contain its own ffconf.h.
 - Included ffconf.h into diskio.c to enable the selection of physical disk from ffconf.h by macro definition.
 - Conditional compilation of physical disk interfaces in diskio.c.

FreeMASTER Communication Driver

Current version is 3.0.6. Visit <https://www.nxp.com/freemaster> for more information. Reach out for a support at <https://community.nxp.com/community/freemaster>.

- 3.0.0
 - Initial version of FreeMASTER driver reworked from a standalone package to MCUXpresso SDK middleware.
 - This driver version supports new version V4 of FreeMASTER serial communication protocol.
 - Supports UART, LPUART, USART, MINIUSART, FlexCAN, USB-CDC and JTAG/BDM communication.
 - Initial version was tested with the following boards: evkmimxrt1060, frdmk64f, frdmke15z, frdmkl128z, lpcxpresso54628 lpcxpresso55s69, lpcxpresso845max and twrk64f120m.
 - Use with FreeMASTER PC Host tool version 2.5 or later.
- 3.0.1
 - FreeMASTER driver extended to support wide range of Kinetis, LPC and i.MX-RT platforms.
 - Low-level communication drivers also available for few non-SDK NXP platforms like S12Z, S32x and more.
 - Use with FreeMASTER PC Host tool version 3.0 or later.
- 3.0.2
 - FreeMASTER driver support of DSC56F800EX and S12 platforms extended.
 - Removed dependency on C99 compiler features.
 - Use with FreeMASTER PC Host tool version 3.0.2 or later.
- 3.0.3
 - General update for SDK 2.9.0
 - fmstr_any demo added to selected platforms - use with MCUXpresso SDK and FreeMASTER peripheral configuration tool.
 - New example.pmp project file embedded into application flash storage.

- USB-CDC implementation fixed, new JTAG EOnCE communication interface added to DSC 56F800E family.
- Use with FreeMASTER PC Host tool version 3.0.3 or later. Version 3.1.x is recommended.
- 3.0.4
 - Fixed component dependency logic of FreeMASTER driver.
 - Use with FreeMASTER PC Host tool version 3.1.x
- 3.0.5
 - General update for SDK 2.11 and 2.12
 - New TCP and UDP support with lwIP stack
 - New communication over Segger RTT interface
 - Add fmstr_net and fmstr_wifi examples for selected i.MX-RT platforms
 - Add fmstr_rtt example for selected platforms
 - Fixed negative recorder threshold trigger processing
- 3.0.6
 - General update for SDK 2.13
 - Use of new Ethernet MDIO driver concept.
 - Support of ENET and NETC Ethernet modules in the fmstr_net example application.
- 3.0.7
 - General update for SDK 2.14

mbedTLS for MCUXpresso SDK

The current version of mbedTLS is based on mbed TLS 2.28.3 branch released 2023-03-28

- 2.28.1
 - New features:
 - * Ported mbedTLS 2.28.3 to SDK.
- 2.28.1
 - New features:
 - * Ported mbedTLS 2.28.1 to SDK.
- 2.28.0
 - New features:
 - * Ported mbedTLS 2.28.0 to SDK.
- 2.27.0
 - New features:
 - * Ported mbedTLS 2.27.0 to SDK.
- 2.26.0
 - New features:
 - * Ported mbedTLS 2.26.0 to SDK.

2.16.6_rev7

- Bug fixes:
 - Corrected definition of global variable g_isCryptoHWInitialized to be only internal static variable in sssapi_mbedtls.c file.

2.16.6_rev6

- Bug fixes:
 - Adding #ifdef in ecdsa.c to remove warning: "function "derive_mpi" was declared but never referenced", when alternative implementation of ECDSA sign and verify is used and not used Deterministic ECDSA, then was derive_mpi function never used.

NTAG I2C plus library

The current version is 1.0.0.

- 1.0.0
 - initial release.

Trusted Firmware M (TF-M) for MCUXpresso SDK

The current version is based on TF-M v1.8.0, released 2023-04-27(35ac80c8581d483da7d18cb8bcd20aaed096550c) on <https://git.trustedfirmware.org/TF-M/trusted-firmware-m.git>

- 1.8.0
 - Ported TF-M v1.8.0 to MCUXpresso SDK. Based on the 2023-04-27 snapshot(35ac80c8581d483da7d18cb8bcd20aaed096550c)
 - Added lpcxpresso55s36 platform.
- 1.7.0
 - Ported TF-M v1.7.0 to MCUXpresso SDK. Based on the 2023-04-04 snapshot(60c4936a7bb3f56bdb50b03)
 - Added lpcxpresso55s36 platform.
- 1.6.0
 - Ported TF-M v1.6.0 to MCUXpresso SDK. Based on the 2022-08-29 snapshot(a5048fb687e4fbf28f9aac69)
 - Added lpcxpresso55s36 platform.
- 1.5.0
 - Ported TF-M v1.5.0 to MCUXpresso SDK. Based on the 2022-03-11 snapshot(47c26ecd0dec177fe2ddf82)
- 1.4.0
 - Ported TF-M v1.4.0 to MCUXpresso SDK. Based on the 2021-08-30 snapshot(00c1106624d733aade4486)
- 1.3.0
 - Ported TF-M v1.3.0 to MCUXpresso SDK. Based on the 2021-04-13 snapshot(cad01ab98c34bb3a13ab49c)
 - Added evkmimxrt685 platform.
 - Added evkmimxrt595 platform.
- 1.1
 - Ported TF-M v1.1 to MCUXpresso SDK. Based on the 2020-08-19 snapshot(54507b1645087e92b5a11591)
- 1.0 Rev3
 - Ported TF-M v1.0 to MCUXpresso SDK. Based on the 2020-04-20 snapshot(1e089705899ff68c617cc0c01)
 - Added HUK derivation function.
- 1.0 Rev2
 - Ported TF-M v1.0 to MCUXpresso SDK. Based on the 2020-04-06 snapshot(d4ac5d14e74d1aa2a78526aa)
 - Added the LPC55S Flash module support for ITS and PS.
 - Added lpcxpresso55s16 platform.

- 1.0 Rev1
 - Ported TF-M v1.0-RC1 to MCUXpresso SDK. Based on the 2019-09-23 snapshot(011c0ad0e76d62bd6f2d
 - Added MCUx and GCC demo applications.
 - Added PSA test suite application.
 - Used mbedCrypto instead of mbedTLS
- 1.0
 - Ported TF-M v1.0-beta to MCUXpresso SDK. Based on the 2019-03-13 snapshot(a5a2a5bc32bc50f4def8d
 - Added lpcpresso55s69 platform.
 - Added MDK demo applications.
 - Bug Fixes:
 - * Fixed compilation warnings and errors.
 - * Changes in the TF-M original source code are marked by the "NXP" comment.

USB stack for MCUXpresso SDK

The current version of USB stack is 2.8.4.

- 2.8.4
 - Improvement:
 - * Add the new netc adatper for the new netc driver.
 - * Fix issues for USB device dfu and usb device msc when enable the macro USB_DEVICE_CONFIG_RETURN_VALUE_CHECK.
 - * Change the header file including order for usb.h header.
 - * Update the USB host audio class driver to fix the wrong output log.
 - * Add the workaround on dev_hid_mouse_bm case for the errata TN00071.
 - * Enable ROOT2 macro in USB device stack.
 - * Use an unified definiton for the base address of RTxxxx platforms.
- 2.8.3
 - Improvement:
 - * Update the EHCI controller driver to support the address convert for TCM.
 - * Update the USB host EHCI controller driver to make sure the mutual exclusion access under multiple tasks' environment.
- 2.8.2
 - Improvement:
 - * Fix noise issue of UAC 3.1, UAC 5.1, UAC 7.1 on usb audio speaker demo.
 - * Fix the issue that incorrect PC behavior when ejecting USB MSC devices.
 - * Update the EHCI controller driver to support RW610 that does not reply on PHY driver, especially for low power feature.
 - * Update the USB_HostHelperParseAlternateSetting to fix the wrong interface parse.
 - * Update dev_composite_hid_audio_unified_bm demo to support independent mute/unmute and volume control.
- 2.8.1
 - Improvement:
 - * update USB audio demos to use audio component (components).

- * Add the checking of function call return value.
- * Add audio multiple channels demo (usb_device_composite_audio_multi_ch_unified) on RT600 audio board.
- * Fix audio noise on sync mode and improve overflow/underflow checking method.
- * Support UAC 3.1, 5.1 and 7.1 on audio speaker demo.
- * Set USB device CDC demo not to depend on DTR setting from host.
- * Support MCUX toolchain on some RTxxxx platforms.
- 2.8.0
 - Improvement:
 - * Fix the USB device stack vulnerability issues.
 - * Update the audio PLL and FRO adjustment codes for audio examples in RTxxx, LPC54xxx and LPC55xxx.
 - * Improve the USB PD AMS collision avoidance.
 - * Improve IP3511 controller driver's dedicated ram allocation.
 - * Change the USB_DATA_ALIGN_SIZE to 4 because the controller driver uses the dedicated RAM to do memcpy.
 - New features:
 - * Enable USB host audio recorder demo for mutilple boards.
- 2.7.0
 - Improvement:
 - * Use new feedback solution and low latency playback for usb device speaker demo and unified demos. Add underflow and overflow protection.
 - * Optimize hard code for usb audio demos.
 - * Update Unconstrained Power field in the Sink Capabilities Message according to the external power state.
 - * Fix CVE-2021-38258 and CVE-2021-38260
 - New features:
 - * Enable USB host video demo for mutilple boards.
 - * Enable USB device MTP demo for mutilple boards.
 - * Add PPS message to usb pd stack.
- 2.6.1
 - Improvement:
 - * rename sdcard as disk for all of sdcard demos. For ramdisk demos, they are not changed.
 - * add wrapper for all of disk demos to support emmc.
- 2.6.0
 - Improvement:
 - * Added more ufi event to support dynamic sdcard capacity.
 - * Passed MISRA-2012 mandatory and required rules.
 - Except rule 17.2 in host hub and otg stack.
 - Except rule 5.1, rule 5.4, rule 21.1 and rule 21.2.
 - * Re-implemented USB components and supported NPW.
 - * Improved IP3511 controller driver's cancelling transfer function.
 - * Enabled the audio2.0 defaultly for device audio demos.
 - * Enabled the host audio2.0 function in host audio class driver and host audio speaker demo.
 - New features:

- * enable two USB controllers in one USB host mouse demo which named as host_hid_mouse_dual.
- * enable UAC 5.1 for usb device audio speaker demo.
- 2.5.0
 - Improvement:
 - * Integrated sdk components (OSA, Timer, GPIO and serial_manager) to USB stack and demos.
 - * Improved the ip3511 driver throughput.
 - * Improved audio initialization codes after SDK audio drivers update.
 - * Improved audio to support the audio2.0 in win10.
 - * Add one "enumeration fail" callback event to host stack.
- 2.4.2
 - Improvement:
 - * Put the USB controller data and transfer buffer to noncache section, removed the setting that sets the whole ocram and sdram as noncached.
 - * Separated composite audio examples' channel,sample rate,format parameters from common macro to in dedicated macro and out dedicated macro.
 - * replaced USB_PrepareData with USB_AudioRecorderGetBuffer.
- 2.4.1
 - New features:
 - * Added enumeration fail callback to host stack when the attached device's enumeration failed.
- 2.4.0
 - Improvement:
 - * Device Charger Detection (DCD) software architecture was refactored.
 - New features:
 - * Enabled Device Charger Detection (DCD) on RT1060.
 - * Enabled Device Charger Detection on RT600.
 - * Enabled host battery charger function on RT600.
- 2.3.0
 - New features:
 - * Added host video camera support. example: usb_host_video_camera
 - * Added a new device example. example: usb_device_composite_cdc_hid_audio_unified
- 2.2.0
 - New features:
 - * Added device DFU support.
 - * Supported OM13790DOCK on LPCXpresso54018.
 - * Added multiple logical unit support in msc class driver, updated usb_device_lba_information_struct_t to support this.
 - * Supported multiple transfers for host ISO on IP3516HS.
 - Bug fixes:
 - * Fixed device ip3511 prime data length than maxpacket size issue.
 - * Initialized interval attribute in usb_device_endpoint_struct_t/usb_device_endpoint_init_struct_t.
 - * Removed unnecessary header file in device CDC class driver, removed unnecessary usb_

- echo, and added DEBUG macro for necessary usb_echo in device CDC class driver.
 - * Fixed device IP3511HS unfinished interrupt transfer missing issue.
- 2.1.0
 - New features:
 - * Added host RNDIS support. example: lwip_dhcp_usb
 - * Enabled USB 3.0 support on device stack.
 - * Power Delivery feature: Added OM13790HOST support; Added auto policy feature; Printed e-marked cable information;
- 2.0.1
 - Bug fixes:
 - * Fixed some USB issues: Fixed MSC CV test failed in MSC examples.
 - * Changed audio codec interfaces.
- 2.0.0
 - New features:
 - * PTN5110N support.
 - Bug fix:
 - * Added some comments, fixed some minor USB issues.
- 1.9.0
 - New features:
 - * Examples:
 - usb_pd_alt_mode_dp_host
- 1.8.2
 - Updated license.
- 1.8.1
 - Bug fix:
 - * Verified some hardware issues, support aruba_flashless.
- 1.8.0
 - New features:
 - * Examples:
 - usb_device_composite_cdc_vcom_cdc_vcom
 - usb_device_composite_hid_audio_unified
 - usb_pd_sink_battery
 - Changed usb_pd_battery to usb_pd_charger_battery.
 - Bug fix:
 - * Code clean up, removed some irrelevant code.
- 1.7.0
 - New features:
 - * USB PD stack support.
 - Examples:
 - * usb_pd
 - * usb_pd_battery
 - * usb_pd_source_charger
- 1.6.3
 - Bug fix: -IP3511_HS driver control transfer sequence issue, enabled 3511 ip cv test.
- 1.6.2

- New features:
 - * Multi instance support.
- 1.6.1
 - New features:
 - Changed the struct variable address method for device_video_virtual_camera and host_phdc_manager.
- 1.6.0
 - New features:
 - * Supported Device Charger Detect feature on usb_device_hid_mouse.
- 1.5.0
 - New features:
 - * Supported controllers
 - OHCI (Full Speed, Host mode)
 - IP3516 (High Speed, Host mode)
 - IP3511 (High Speed, Device mode)
 - * Examples:
 - usb_lpm_device_hid_mouse
 - usb_lpm_device_hid_mouse_lite
 - usb_lpm_host_hid_mouse
- 1.4.0
 - New features:
 - * Examples:
 - usb_device_hid_mouse/freertos_static
 - usb_suspend_resume_device_hid_mouse_lite
- 1.3.0
 - New features:
 - * Supported roles
 - OTG
 - * Supported classes
 - CDC RNDIS
 - * Examples
 - usb_otg_hid_mouse
 - usb_device_cdc_vnic
 - usb_suspend_resume_device_hid_mouse
 - usb_suspend_resume_host_hid_mouse
- 1.2.0
 - New features:
 - * Supported controllers
 - LPC IP3511 (Full Speed, Device mode)
- 1.1.0
 - Bug fix:
 - * Fixed some issues in USB certification.
 - * Changed VID and Manufacturer string to NXP.
 - New features:
 - * Supported classes

- Pinter
- * Examples:
 - usb_device_composite_cdc_msc_sdcard
 - usb_device_printer_virtual_plain_text
 - usb_host_printer_plain_text
- 1.0.1
 - Bug fix:
 - * Improved the efficiency of device audio speaker by changing the transfer mode from interrupt to DMA, thus providing the ability to eliminate the periodic noise.
- 1.0.0
 - New features:
 - * Supported roles
 - Device
 - Host
 - * Supported controllers:
 - KHCI (Full Speed)
 - EHCI (High Speed)
 - * Supported classes:
 - AUDIO
 - CCID
 - CDC
 - HID
 - MSC
 - PHDC
 - VIDEO
 - * Examples:
 - usb_device_audio_generator
 - usb_device_audio_speaker
 - usb_device_ccid_smart_card
 - usb_device_cdc_vcom
 - usb_device_cdc_vnic
 - usb_device_composite_cdc_msc
 - usb_device_composite_hid_audio
 - usb_device_composite_hid_mouse_hid_keyboard
 - usb_device_hid_generic
 - usb_device_hid_mouse
 - usb_device_msc_ramdisk
 - usb_device_msc_sdcard
 - usb_device_phdc_weighscale
 - usb_device_video_flexio_ov7670
 - usb_device_video_virtual_camera
 - usb_host_audio_speaker
 - usb_host_cdc
 - usb_host_hid_generic
 - usb_host_hid_mouse

- usb_host_hid_mouse_keyboard
- usb_host_msdc_command
- usb_host_msdc_fatfs
- usb_host_phdc_manager
- usb_keyboard2mouse
- usb_pin_detect_hid_mouse

3 Component Change Log

CODEC

The current codec common driver version is 2.3.1.

- 2.3.1
 - Bug Fixes
 - * Fixed violations of MISRA C-2012 rule 16.1,16.3.
- 2.3.0
 - Improvements
 - * Added enum `_codec_volume_capability` for `CODEC_SetVolume/CODEC_SetMute` to cover more volume configurations.
- 2.2.2
 - Bug Fixes
 - * Fixed the typo in codec common driver.
- 2.2.1
 - Bug Fixes
 - * Fixed violations of MISRA C-2012 rule 10.3, 8.3, 10.7, 17.7.
- 2.2.0
 - Improvements
 - * Used `HAL_CODEC_HANDLER_SIZE` which is determined by low level driver instead of use `CODEC_HANDLE_SIZE` for the codec device handle definition.
- 2.1.1
 - Improvements
 - * Supported all of the codec in the codec adapter.
 - * Modified the codec handle definition to improve user experience.
 - * Modified the capability member type from entity to pointer in codec handle.
 - Bug Fixes
 - * Fixed the Coverity issue regrading array compared against 0.
- 2.1.0
 - Deprecated APIs
 - * `CODEC_GetMappedFormatBits`
 - * `CODEC_I2C_WriteReg`
 - * `CODEC_I2C_ReadReg`
 - * `CODEC_I2C_ModifyReg`
 - * `CODEC_SetEncoding`
 - new APIs
 - * `CODEC_SetPower`
 - * `CODEC_SetVolume`
 - * `CODEC_SetMute`
 - * `CODEC_SetPlay`
 - * `CODEC_SetRecord`
 - * `CODEC_SetRecordChannel`

- * CODEC_ModuleControl
- new features
 - * Removed duplicate members in codec_handle_t and codec_config_t.
 - * Added codec_config_t pointer in codec_handle_t.
 - * Added codec capability flag in codec_handle_t.
 - * Used codec adapter instead of function pointer in codec common driver.
- 2.0.1
 - Added delayMs function pointer in codec handle.
- 2.0.0
 - Initial version.

SERIAL_MANAGER

The current Serial_Manager component version is 1.0.2.

- 1.0.2
 - Add SerialManager_WriteTimeDelay()/SerialManager_ReadTimeDelay() for serial manager's read/write non-blocking mode.
- 1.0.1
 - Add prefixing fsl_component_xxx/fsl_adapter_xxx.
- 1.0.0
 - Initial version

How to Reach Us:**Home Page:**

nxp.com

Web Support:

nxp.com/support

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: nxp.com/SalesTermsandConditions.

While NXP has implemented advanced security features, all products may be subject to unidentified vulnerabilities. Customers are responsible for the design and operation of their applications and products to reduce the effect of these vulnerabilities on customer's applications and products, and NXP accepts no liability for any vulnerability that is discovered. Customers should implement appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP, the NXP logo, NXP SECURE CONNECTIONS FOR A SMARTER WORLD, Freescale, the Freescale logo, Kinetis, Processor Expert, and Tower are trademarks of NXP B.V. All other product or service names are the property of their respective owners. Arm, Cortex, Keil, Mbed, Mbed Enabled, and Vision are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org.

© 2021 NXP B.V.

