

TN00041

USBD Library for LPC4300/LPC1800 series MCUs

1.0 — 9 July 2018

Technical note

Document information

Info	Content
Keywords	USBD library source code, LPC, USB stack.
Abstract	This technical note describes the history of USBD ROM device driver stack, the differences between LPC4300/LPC1800 series and the rest of the MCUs with USB controller, releases of the latest USBD library source with bug fixes, and new features. The latest USBD library supports most of the LPC family MCUs including LPC1100 series, LPC1500 series, LPC4300/LPC1800 series, and LPC54000 series. This package works with LPC4300 and LPC1800 series only.



Revision history

Rev	Date	Description
1.0	20180709	Initial version.

Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

1. Introduction

The ROM-based USB driver is provided as part of the boot ROM since LPC4300 and LPC1800 series MCUs are widely adopted by many users.

The ROM contains flexible USB device stack to simplify the USB application development. The USB ROM stack has built-in support for Communication Device Class (CDC), the Human Interface Device (HID), the Mass Storage Class (MSC), and Device Firmware Upgrade (DFU) class. It also supports a composite device model consisting of multiple interfaces of these supported classes. However, there are limitations in the earlier version of the USB driver and some known issues have been identified by both NXP and end users over time. Work-arounds are offered wherever possible and described in the errata sheets because NXP cannot provide instant ROM update for every USB driver issue found. Hardware features, such as Link Power Management (LPM) were not supported in the earlier version of the USB ROM, therefore, no work-around is provided.

The ROM based USB driver simplifies the USB application development. However, it makes debugging a complex USB class driver more difficult. In addition, some USB ROM work-arounds require more RAM resources.

MCUs with larger flash memory size links the USB library components directly, speeding up development time and enabling easier debugging. This removes any required work-around. NXP publishes two versions of the USB driver stack source code:

- Original version residing in the MCU ROM as references.
- Updated version, also called USB library, with bug fixes on all known issues and new features.

Some of the key new features of the USB library include:

- Link Power Management (LPM) Support (not applicable to LPC4300 and LPC1800 MCUs)
- MSC class enhancement allowing access to larger memory media greater than 4GB.
- Device Core stack update including Root 2 test (Microsoft XBOX compliance) support.
- Enhancement to DFU class to support multiple alternate interfaces.
- String descriptor callback. To provide customer string descriptors not present in descriptor array for random indexed strings.

Two packages of the USB libraries are published. Although the stack level of the device driver shares the same source code, the low-level drivers for LPC4300/LPC1800 series and LPC1100/LPC1500 series are different. See Table xx

Table 1. USB IPs used in LPC family MCUs

MCUs\Feature	Speed	Maximum number of EPs	Link Power Management (LPM)	USB IP name
LPC1100/LPC1500 series	FS only	5	Yes	IP351x
LPC54100 series	FS only	5	Yes	IP351x
LPC54100 series	FS only	5	Yes	IP351x
LPC54600 series	Both HS (port 1) and FS (port 0). The HS controller cannot be forced to FS in the device driver	HS: 6 FS: 5	Yes	IP351x

The following section gives an overview of the USB library and how to use the USB library to build a USB application for LPC4300/LPC1800 series MCUs.

2. Description

During the early stages of the USB controller integration, Keil and NXP worked together towards the USB driver software support solution. Since then, NXP has added more low-level drivers to support different USB IPs. In addition, several new features, such as, Link Power Management (LPM) support, DFU class support, improved memory management, callbacks to make the USB stack more user friendly, and bug fixes, are now included.

The following figure shows the architectural block diagram of the USB device ROM stack. The stack consists of three main layers:

1. The Class Layer
2. The USB Core Layer
3. The Device Controller Driver Layer




Fig 1. USB device ROM stack block diagram

The source files of the updated USB library are built and tested on Keil, IAR, and MCUXpresso IDEs using LPCXpresso Development Board.

For the User Manual of LPCXpresso Development Board for LPC4300 MCUs, see:

<https://www.nxp.com/support/developer-resources/hardware-development-tools/lpcxpresso-boards/lpcxpresso4367-development-board:OM13088>

The USB library package provided with this technical note is based on the LPCOpen (version 3) for LPC4300:

<https://www.nxp.com/products/processors-and-microcontrollers/arm-based-processors-and-mcus/lpc-cortex-m-mcus/lpc4300-cortex-m4-m0/lpcopen-software-development-platform-lpc43xx:LPCOPEN-SOFTWARE-FOR-LPC43XX?srch=1&sr=3&pageNum=1>

“usbd_rom_lpc43xx” directory contains the source of the original USB stack residing in the ROM. **Since it is unmodified from the LPC43xx/LPC18xx ROM, it contains all the known issues of the USB ROM device driver stack listed in the LPC43xx/LPC18xx Errata and must be used as reference only.**

Note: For the ROM release, the source files of the USB ROM driver were built on the Keil MDK. Some of the directives and keywords in the source are for Keil compiler only and may not work on other compilers.

“usbd_lib_lpc43xx” directory contains the latest USB stack library with the known issues from USB ROM fixed. It also contains the LPCOpen.USB class examples using USB library API calls.

In the “usbd_lib_lpc43xx” directory, “LPC_USB Lib” contains the latest USB stack library and the rest are the USB class examples making use of the USB library. An

identical LPCOpen (version 3) directory structure is applied to these USB class examples.

The USB examples are available in three tool chains:

- IAR embedded Workbench
- Keil MDK
- MCUXpresso

The USB library can be found under:

`\usbd_lib_lpc43xx\prj_lpc_usbd_lib`

The USB class examples can be found under:

`\usbd_lib_lpc43xx\prj_xpresso4337`

The USB library documentation (revision 2.0) in HTML format is under:

`\usbd_lib_lpc43xx\LPC_USBD_Lib\docs\html`

Click `\usbd_lib_lpc43xx\LPC_USBD_Lib\docs\html\index.html` to start.

If using Internet Explorer, click “Allow block Content” to allow page to run script and active X control.

It is important to note that there are differences between the library documentation and the Section “USB ROM API” of the User Manual. The key difference is related to USB_API_INIT_PARAM data structure defined in “chip_43xx_l8xx\usbd_lib” directory where all the new features are added.

Under “\LPC_USBD_Lib\mw_usbd” directory, mw_usbd_rom.c has the version identifier of the latest USB library stack.

Follow the “LPCOpen Quick Start Guide for all platforms” to build chip and board libraries first under “lib_chip_lpcxxx” and “lib_board_lpcxxx”. Then, build the USB library under “LPC_USBD_Lib”. Finally, build your USB class application under “prj_xpresso4337” directory.

Now, the USB class application links the USB library APIs instead of the USB ROM APIs and are ready to execute.

3. Legal information

3.1 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

3.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or

malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

3.3 Trademarks

Notice: All referenced brands, product names, service names and trademarks are property of their respective owners.

4. Contents

1. Introduction3

2. Description.....4

3. Legal information7

3.1 Definitions7

3.2 Disclaimers.....7

3.3 Trademarks.....7

4. Contents.....8

Please be aware that important notices concerning this document and the product(s) described herein, have been included in the section 'Legal information'.